
GSC375S5-II | GSC375D5-II

Powered by SDEC

Genlitec® Power & Lighting Solutions





■ Generator Specification

Service	PRP(1)	ESP(2)
Power (KVA)	375	413
Power (KW)	300	330
Rated speed	1500RPM	
Standard voltage	400/230V	
Power factor	0.8	
Phase	3	

Performance Data		
Model		GSC375S5-II | GSC375D5-II
Engine brand		**SDEC**
Engine model		SC13E500D2
Speed control type		Electronic
Alternator brand		**GENLITEC**
Alternator model		S314G300
Control system		**SMARTGEN** HGM6120N
Starter motor voltage		24V
Frequency		50Hz
Fuel Consumption (L/H)	100% Prime Load	81.0
	75% Prime Load	59.3
	50% Prime Load	40.9
	25% Prime Load	23.1
	Fuel Tank (L)	570

ISO CE

GENLITEC Power gensets are compliant with ISO 9001 and CE standard, which include the following directives:

- 2006/42/EC Machinery directive
- 2014/30/EU Electromagnetic compatibility directive
- EN 12100:2010; EN ISO 8528-13:2016; EN 60204-1:2018; EN 61000-6-2:2019; EN 61000-6-4:2019
- **GSC375S5-II (Silent Type)**
- **GSC375D5-II (Open Type)**

(1) PRP (Prime Power)

According to ISO 8528-1, prime power is the maximum power available during a variable power sequence, which may be run for an unlimited number of hours per year, between stated maintenance intervals. The permissible average power output during at 24 hours period shall not exceed 80% of the prime power. 10% overload available for governing purposes only.

(2) ESP (Standby Power)


According to ISO 8528-1. It is defined as the maximum power available, under the agreed operating conditions, for which the generating set can deliver for up to 500 hours of operation per year (of which no more than 300 hours for continuative use) with the maintenance intervals and procedures being carried out as prescribed by the manufactures. No overload capability is available.

Voltage (V)	ESP		PRP		Current
	KVA	KW	KVA	KW	Amps
415/240	413	330	375	300	521.7
400/230	413	330	375	300	541.3
380/220	413	330	375	300	569.8

Standard Reference Conditions

Note: Standard reference condition 25℃ (77°F) air inlet temp. 100m (328ft) A.S.L 30% relative humidity. Fuel consumption date with diesel fuel with specific gravity of 0.85 and conforming to BS 2869: 1998 Class A2

Dimension & Weight





Dimension	Open type	Silent type
Length (L)	3200mm	4150mm
Width (W)	1200mm	1400mm
Height (H)	1800mm	2230mm
Net Weight	3100kg	4230kg

Note: This parameter allows for some acceptable deviations.

GENLITEC POWER has the right to modify any feature without prior notice, Weights and dimensions based on standard products. Illustrations may include optional equipment. Technical data described in this document correspond to the available information at the moment of printing. The illustrations and images are indicative and may not coincide in their entirety with the product.

GSC375S5-II | GSC375D5-II

Powered by SDEC

Genlitec®
Power & Lighting Solutions

■ Engine Specification



MODEL: SDEC SC15E500D2	
Cylinder number	6
Aspiration system	Turbo, air-air intercooled
Cooling method	Water cooled
Governor type	Electronic
Bore x Stroke (mm)	130 x 161
Compression ratio	17:1
Rated speed (RPM)	1500
Displacement (L)	12.8
Rated power (KW)	339
Standby power (KW)	373
Fuel system	Direct injection
Coolant capacity (L)	23.2（Engine Only）
Oil capacity (L)	36
Max. water temperature	104℃
Starter motor capacity	DC 24V

■ Alternator Specification



MODEL: GENLITEC S314G300	
Number of phase	3
Rated power (KW/KVA)	300/373
Frequency (Hz)	50
Power factor (Cos Phi)	0.8
Poles	4
Temp. rise	125K
Terminals	6 (12 leads for option)
Insulation type	H class
Ambient temp.	40℃
IP rating	IP23
Excitation system	Self-excited
Bearing	Single bearing
Coating	Vacuum impregnation
Voltage regulator	A.V.R
Coupling	Flexible disc

Standard Supply Scope

- Industrial exhaust silencer
- Maintenance free battery
- Water cooling radiator
- A.V.R
- Flexible pipes
- Battery wires
- Wiring diagram
- Build-in based fuel tank
- Float Battery charger
- Manual books
- Tool kits
- Emergency stop button
- Base frame
- Digital control panel
- Main circuit breaker

■ Optional Supply Scope

Engine	Alternator	Generator Sets	Control Panel
O Water jacket pre-heater	O Anti-condensation heater	O Extended fuel tank	O Remote control system
O Lubrication oil pre-heater	O AREP & PMG	O **C-Type** Soundproof canopy	O ATS panel
O Battery isolator	O **STAMFORD** alternator	O **D-Type** Soundproof canopy	O Synchronizing System
	O **LEROY SOMER** alternator		

■ Warranty Period

SDEC diesel engine: Factory warranty, 2 months or 1000 working hours.
STAMFORD/LEROY SOMER alternator: Global warranty, 12 months or 1000 working hours.
GENLITEC alternator: Factory warranty, 12 months or 1000 working hours.

GSC375S5-II | GSC375D5-II

Powered by SDEC

Genlitec® Power & Lighting Solutions

■ Control Panel

Configuration
● Emergency stop button
● Protection MCB (Main circuit breaker)
● Float battery charger
● ATS connection
● AMF digital control module
● Fuel level meter
● Controller power switch
● Alarm buzzer



Features
● Chinese, English, Spanish, Turkish, Russian & French
● Three phase generator monitoring
● Automatic or manual start/stop of the gensets
● Push buttons for simple control & operation
● Generator measurements (50Hz/60Hz)
● Precision collect & display parameters about ENGINE
● Comprehensive shutdown or warning on fault condition
● Three phase generator protections
- Over / under voltage
- Over / under frequency
- Current / voltage asymmetry
- Over current / overload
● Three phase AMF function
- Over / under voltage
- Loss of phase detection function
● Emergency start function
● IP55 waterproof with rubber-ring gasket

Control Module Model: SMARTGEN HGM6120N	
Display	LCD (132 x 64)
Operation panel	Silicon rubber
Digital input	5
Relay output	6
Analogue input	3
AMF	Yes
AC System	1P2W / 2P3W / 3P3W / 3P4W
Alternator voltage	15-360V (ph-N)
Alternator frequency	50/60Hz
KW/Amp Detecting & Display	Yes
Monitor interface	USB
Programmable interface	USB
DC supply	DC 8-35V
Operating temp.	-25 ~ +70℃

■ Controller Module Options

COMAP	DEIF	DEEPSEA
AMF25	SGC 420	DSE7320
		

Genlitec® Power & Lighting Solutions

GENLITEC POWER TECHNOLOGY CO., LTD.
GENLITEC (FUZHOU) POWER EQUIPMET CO., LTD.
marketing@genlitec.com | www.genlitecpower.com

Local Distributor / Partner

All information in the document is substantially correct at the time of printing
But may be subsequently altered by the company.