
# GSC363S5 | GSC363D5

Powered by SDEC

Genlitec® Power & Lighting Solutions




## ■ Generator Specification

| Service | PRP(1) | ESP(2) |
|---|---|---|
| Power (KVA) | 363 | 400 |
| Power (KW) | 290 | 320 |
| Rated speed | 1500RPM | |
| Standard voltage | 400/230V | |
| Power factor | 0.8 | |
| Phase | 3 | |

| Performance Data | | |
|---|---|---|
| Model | | GSC363S5 \| GSC363D5 |
| Engine brand | | **SDEC** |
| Engine model | | SC12E480D2 |
| Speed control type | | Electronic |
| Alternator brand | | **GENLITEC** |
| Alternator model | | S314G300 |
| Control system | | **SMARTGEN** HGM6120N |
| Starter motor voltage | | 24V |
| Frequency | | 50Hz |
| Fuel Consumption (L/H) | 100% Prime Load | 77.2 |
| | 75% Prime Load | 56.5 |
| | 50% Prime Load | 38.9 |
| | 25% Prime Load | 22.0 |
| Fuel Tank (L) | | 550 |

ISO CE

GENLITEC Power gensets are compliant with ISO 9001 and CE standard, which include the following directives:

- 2006/42/EC Machinery directive
- 2014/30/EU Electromagnetic compatibility directive
- EN 12100:2010; EN ISO 8528-13:2016; EN 60204-1:2018; EN 61000-6-2:2019; EN 61000-6-4:2019
- **GSC363S5 (Silent Type)**
- **GSC363D5 (Open Type)**

**(1) PRP (Prime Power)**

According to ISO 8528-1, prime power is the maximum power available during a variable power sequence, which may be run for an unlimited number of hours per year, between stated maintenance intervals. The permissible average power output during at 24 hours period shall not exceed 80% of the prime power. 10% overload available for governing purposes only.

**(2) ESP (Standby Power)**


According to ISO 8528-1. It is defined as the maximum power available, under the agreed operating conditions, for which the generating set can deliver for up to 500 hours of operation per year (of which no more than 300 hours for continuative use) with the maintenance intervals and procedures being carried out as prescribed by the manufactures. No overload capability is available.


| Voltage (V) | ESP | | PRP | | Current |
|---|---|---|---|---|---|
| | KVA | KW | KVA | KW | Amps |
| 415/240 | 400 | 320 | 363 | 290 | 505 |
| 400/230 | 400 | 320 | 363 | 290 | 524 |
| 380/220 | 400 | 320 | 363 | 290 | 551.5 |

**Standard Reference Conditions**

Note: Standard reference condition 25℃ (77°F) air inlet temp. 100m (328ft) A.S.L 30% relative humidity. Fuel consumption date with diesel fuel with specific gravity of 0.85 and conforming to BS 2869: 1998 Class A2

## Dimension & Weight




| Dimension | Open type | Silent type |
|---|---|---|
| Length (L) | 3100mm | 4050mm |
| Width (W) | 1200mm | 1400mm |
| Height (H) | 1800mm | 2150mm |
| Net Weight | 2850kg | 4000kg |

**Note: This parameter allows for some acceptable deviations.**

**GENLITEC POWER** has the right to modify any feature without prior notice, Weights and dimensions based on standard products. Illustrations may include optional equipment. Technical data described in this document correspond to the available information at the moment of printing. The illustrations and images are indicative and may not coincide in their entirety with the product.

# GSC363S5 | GSC363D5

Powered by SDEC

Genlitec® Power & Lighting Solutions

## ■ Engine Specification



| MODEL: SDEC SC12E480D2 | |
|---|---|
| Cylinder number | 6 |
| Aspiration system | Turbo, air-air intercooled |
| Cooling method | Water cooled |
| Governor type | Electronic |
| Bore x Stroke (mm) | 128 x 153 |
| Compression ratio | 17:1 |
| Rated speed (RPM) | 1500 |
| Displacement (L) | 11.8 |
| Rated power (KW) | 323 |
| Standby power (KW) | 355 |
| Fuel system | Direct injection |
| Coolant capacity (L) | 23.2（Engine Only） |
| Oil capacity (L) | 36 |
| Max. water temperature | 104℃ |
| Starter motor capacity | DC 24V |

## ■ Alternator Specification




| MODEL: GENLITEC S314G300 | |
|---|---|
| Number of phase | 3 |
| Rated power (KW/KVA) | 300/375 |
| Frequency (Hz) | 50 |
| Power factor (Cos Phi) | 0.8 |
| Poles | 4 |
| Temp. rise | 125K |
| Terminals | 6 (12 leads for option) |
| Insulation type | H class |
| Ambient temp. | 40℃ |
| IP rating | IP23 |
| Excitation system | Self-excited |
| Bearing | Single bearing |
| Coating | Vacuum impregnation |
| Voltage regulator | A.V.R |
| Coupling | Flexible disc |

## Standard Supply Scope

- Industrial exhaust silencer
- Maintenance free battery
- Water cooling radiator
- A.V.R
- Flexible pipes
- Battery wires
- Wiring diagram
- Build-in based fuel tank
- Float Battery charger
- Manual books
- Tool kits
- Emergency stop button
- Base frame
- Digital control panel
- Main circuit breaker

## ■ Optional Supply Scope

| Engine | Alternator | Generator Sets | Control Panel |
|---|---|---|---|
| O Water jacket pre-heater | O Anti-condensation heater | O Extended fuel tank | O Remote control system |
| O Lubrication oil pre-heater | O AREP & PMG | O **C-Type** Soundproof canopy | O ATS panel |
| O Battery isolator | O **STAMFORD** alternator | O **D-Type** Soundproof canopy | O Synchronizing System |
| | O **LEROY SOMER** alternator | | |

## ■ Warranty Period

**SDEC diesel engine:** Factory warranty, 2 months or 1000 working hours.
**STAMFORD/LEROY SOMER alternator:** Global warranty, 12 months or 1000 working hours.
**GENLITEC alternator:** Factory warranty, 12 months or 1000 working hours.

# GSC363S5 | GSC363D5

Powered by SDEC

Genlitec® Power & Lighting Solutions

## ■ Control Panel

| Configuration |
|---|
| ● Emergency stop button |
| ● Protection MCB (Main circuit breaker) |
| ● Float battery charger |
| ● ATS connection |
| ● AMF digital control module |
| ● Fuel level meter |
| ● Controller power switch |
| ● Alarm buzzer |




| Features |
|---|
| ● Chinese, English, Spanish, Turkish, Russian & French |
| ● Three phase generator monitoring |
| ● Automatic or manual start/stop of the gensets |
| ● Push buttons for simple control & operation |
| ● Generator measurements (50Hz/60Hz) |
| ● Precision collect & display parameters about ENGINE |
| ● Comprehensive shutdown or warning on fault condition |
| ● Three phase generator protections |
| - Over / under voltage |
| - Over / under frequency |
| - Current / voltage asymmetry |
| - Over current / overload |
| ● Three phase AMF function |
| - Over / under voltage |
| - Loss of phase detection function |
| ● Emergency start function |
| ● IP55 waterproof with rubber-ring gasket |

| Control Module Model: SMARTGEN HGM6120N | |
|---|---|
| Display | LCD (132 x 64) |
| Operation panel | Silicon rubber |
| Digital input | 5 |
| Relay output | 6 |
| Analogue input | 3 |
| AMF | Yes |
| AC System | 1P2W / 2P3W / 3P3W / 3P4W |
| Alternator voltage | 15-360V (ph-N) |
| Alternator frequency | 50/60Hz |
| KW/Amp Detecting & Display | Yes |
| Monitor interface | USB |
| Programmable interface | USB |
| DC supply | DC 8-35V |
| Operating temp. | -25 ~ +70℃ |

## ■ Controller Module Options

| COMAP | DEIF | DEEPSEA |
|---|---|---|
| AMF25 | SGC 420 | DSE7320 |
|  |  |  |





Genlitec® Power & Lighting Solutions

**GENLITEC POWER TECHNOLOGY CO., LTD.**
**GENLITEC (FUZHOU) POWER EQUIPMET CO., LTD.**
marketing@genlitec.com | www.genlitecpower.com

**Local Distributor / Partner**

All information in the document is substantially correct at the time of printing
But may be subsequently altered by the company.