




Generator Specification

Service	PRP(1)	ESP(2)
Power (KVA)	900	1000
Power (KW)	720	800
Rated speed	1500RPM	
Standard voltage	220/380V	
Power factor	0.8	
Phase	3	



GENLITEC Power gensets are compliant with ISO 9001 and CE standard, which include the following directives:

- 2006/42/EC Machinery safety.
- 2006/95/EC Low voltage
- EN 60204-1: 2006+A1: 2009, EN ISO 12100: 2010, EN ISO 13849-1:2008, EN 12601: 2010
- **GPP900S5: Silent Type**
- **GPP900D5: Open Type**

(1) PRP (Prime Power)

According to ISO 8528-1, prime power is the maximum power available during a variable power sequence, which may be run for an unlimited number of hours per year, between stated maintenance intervals. The permissible average power output during at 24 hours period shall not exceed 80% of the prime power. 10% overload available for governing purposes only.

(2) ESP (Standby Power)

According to ISO 8528-1. It is defined as the maximum power available, under the agreed operating conditions, for which the generating set is capable of delivering for up to 500 hours of operation per year (of which no more than 300 hours for continuative use) with the maintenance intervals and procedures being carried out as prescribed by the manufactures. No overload capability is available.

Voltage (V)	ESP		PRP		Current Amps
	KVA	KW	KVA	KW	
220/380	1000	800	900	720	1367.4
230/400	1000	800	900	720	1299.0
240/415	1000	800	900	720	1252.1


Performance Data

Model	GPP900S5 GPP900D5	
Engine brand	PERKINS	
Engine model	4008TAG1A	
Speed control type	Electronic	
Alternator brand	GENLITEC	
Alternator model	S404G728	
Control system	DEESEA DSE6120 MKII	
Starter motor voltage	24V	
Frequency	50Hz	
Fuel Cons.	100% Prime Load	195 L/hrs
	75% Prime Load	143 L/hrs
	50% Prime Load	98 L/hrs
Fuel tank volume	1000 Liters	

Standard Reference Conditions

Note: Standard reference condition 25°C (77°F) air inlet temp. 100m (328ft) A.S.L 30% relative humidity. Fuel consumption date with diesel fuel with specific gravity of 0.85 and conforming to BS 2869: 1998 Class A2


Dimension & Weight



Dimension	Open type	Silent type
Length (L)	4300mm	5810mm
Width (W)	2050mm	2190mm
Height (H)	2200mm	2550mm
Net Weight	6970kg	9650kg

Note: This parameter allows for some acceptable deviations.

■ Engine Specification



MODEL: PERKINS 4008TAG1A	
Cylinder number	8
Aspiration system	Turbo, air to air charge cooled
Cooling method	Liquid cooled
Governor type	Electronic
Bore x Stroke (mm)	160 x 190
Compression ratio	13.6:1
Rated speed (RPM)	1500
Displacement (L)	30.561
Rated power (KW)	805
Standby power (KW)	882
Oil consumption (g/kw.h)	/
Coolant capacity (L)	153
Oil capacity (L)	149
Combustion system	Direct injection
Starter motor capacity	DC 24V

■ Alternator Specification



MODEL: GENLITEC S404G728	
Number of phase	3
Rated power (KW/KVA)	728/910
Frequency (Hz)	50
Power factor (Cos Phi)	0.8
Poles	4
Temp. rise	125K
Terminals	6 (12-lead for option)
Insulation type	H class
Ambient temp.	40°C
IP rating	IP23
Excitation system	Self-excited
Bearing	Single bearing
Coating	Vacuum impregnation
Voltage regulator	A.V.R
Coupling	Flexible disc

Standard Supply Scope

- Industrial exhaust silencer
 - Maintenance free battery
 - Water cooling radiator
 - A.V.R
- Flexible pipes
 - Battery wires
 - Wiring diagram
 - Build-in based fuel tank
- Float Battery charger
 - Manual books
 - Emergency stop button
- Base frame
 - Digital control panel
 - Main circuit breaker

■ Optional Supply Scope

Engine	Alternator	Generator Sets	Control Panel
○ Water jacket pre-heater ○ Lubrication oil pre-heater ○ Battery isolator	○ Anti-condensation heater ○ PMG ○ AREP ○ STAMFORD alternator ○ LEROY SOMER alternator	○ Galvanized steel enclosure ○ 20GP Containerized enclosure ○ 40HQ Containerized enclosure	○ Remote control system ○ ATS panel ○ Synchronization system

Control Panel

Configuration
● Emergency stop button
● Protection MCB (Main circuit breaker)
● Float battery charger
● ATS connection
● AMF digital control module
● Fuel level meter
● Controller power switch
● Alarm buzzer

Features
● Multiple display languages
● Automatic transfer between mains and generator power
● 3-phase mains and generator voltage monitoring
● Generator current monitoring and protection
● Event log for 10 events and engine-hours counter
● 6 digital inputs and 3 analog sender inputs
● Six outputs; configuration depends on the engine version
● Three phase generator protections
- Over / under voltage
- Over / under frequency
- Current / voltage asymmetry
- Over current / overload
● Three phase AMF function
- Over / under voltage
- Loss of phase detection function
● Emergency start function
● IP65 rating with rubber-ring gasket



Control Module Model: DEEPSEA DSE6120 MKII	
Display	Large back-lit text display
Generator & Mains (Utility)	15 V to 415 V AC (Ph to N)
Voltage Range	26 V to 719 V AC (Ph to Ph)
Frequency range	3.5 Hz to 75 Hz
Analogue inputs A to F	Negative switching
AMF function	Yes
AC System	1P2W / 2P3W / 3P3W / 3P4W
Alternator frequency	50/60Hz
Monitor interface	USB
Programmable interface	USB
DC supply	DC 8-35V
Operating temp.	-30 ~ +70°C

Control Module Certified	
CE	PG
UL LISTED	ISO 9001
UKAS	EGSA
AMPS	IPC MEMBER

Controller Module Options

COMAP	SMARTGEN	DEEPSEA
AMF25	HGM6120N	DSE7320 MKII

