

GLT1600L-8HP

Powered by  Perkins



■ Generator Specification

Service	50Hz	60Hz
Genset PRP (1) (KW)	7.2	8.0
Engine speed	1500RPM	1800RPM
Power factor	1.0	
Phase	Single	
Voltage (V)	110/220; 120/240; 220; 230; 240	



GENLITEC Power lighting towers & generator sets are compliant with ISO 9001 and CE standard, which include the following directives:

- 2006/42/EC Machinery directive
- 2014/30/EU Electromagnetic compatibility directive
- EN 12100:2010; EN ISO 8528-13:2016; EN 60204-1:2018; EN 61000-6-2:2019; EN 61000-6-4:2019

(1) PRP (Prime Power)

According to ISO 8528-1, prime power is the maximum power available during a variable power sequence, which may be run for an unlimited number of hours per year, between stated maintenance intervals. The permissible average power output during at 24 hours period shall not exceed 80% of the prime power. 10% overload available for governing purposes only.

(2) ESP (Standby Power)

According to ISO 8528-1. It is defined as the maximum power available, under the agreed operating conditions, for which the generating set is capable of delivering for up to 500 hours of operation per year (of which no more than 300 hours for continuative use) with the maintenance intervals and procedures being carried out as prescribed by the manufactures. No overload capability is available.

Container Loading Capacity

4 SETS (disassembled**) / 20GP

8 SETS (disassembled**) / 40GP



**dismounted parts: tow bar, wheels, axle, stabilizers




Performance Data	
Model	GLT1600L-8HP
Engine brand	PERKINS
Engine model	403D-11G
Speed control type	Mechanical
Alternator brand	GENLITEC
Alternator model	S164LT8
Control system	SMARTGEN HGM1790N
Starter motor voltage	12V
Max. height of mast	8 meters
Mast lifting/lowing system	Hydraulic
Total power of lamps	4x400 watts LED
Fuel consumption (100% load)	3.0L/H
Fuel tank capacity	115L

Standard Reference Conditions

Note: Standard reference condition 25°C (77°F) air inlet temp. 100m (328ft) A.S.L 30% relative humidity. Fuel consumption date with diesel fuel with specific gravity of 0.85 and conforming to BS 2869: 1998 Class A2

Dimension & Weight



Dimension	Storage	Working
Length (L)	2800mm	2800mm
Width (W)	1440mm	2450mm
Height (H)	2680mm	8000mm
Net Weight	950kg	

Note: This parameter allows for some acceptable deviations.

GLT1600L-8HP

Powered by  Perkins

■ Engine Specification



MODEL: PERKINS 403D-11G	
Cylinder number	3
Aspiration system	Natural
Cooling method	Water cooled
Combustion system	Indirect injection
Bore x Stroke (mm)	77 x 81
Compression ratio	23:1
Rated speed (RPM)	1500/1800
Displacement (L)	1.131
Rated power (KW)	8.6/1500RPM
	10.7/1800RPM
Fuel injection pump	Mechanical pump
Oil capacity (L)	4.9
Total Coolant capacity (L)	5.2
Starter motor capacity	DC 12V

■ Alternator Specification



MODEL: GENLITEC S164LT8	
Number of phases	Single
Rated power (KW)	8
Frequency (Hz)	50/60
Power factor (Cos Phi)	1
Temp. rise	125K
Insulation type	H class
Ambient temp.	40°C
IP rating	IP23
Excitation system	Self-excited
Bearing	Single bearing
Coating	Vacuum impregnation
Voltage regulator	A.V.R
Coupling	Flexible disc

■ Operation Mast Specification

Max. height of mast	8.5m
Elevation system	Hydraulic
Raising/Lowing mast method	Electric Button
Mast stages	8
Mast turning angle	358° manually
Lights tilting angle	0
Mast material	Galvanization Steel tube

○ For options (please contact with GENLITEC sales team for more information)

■ Lamps Specification

Total power of lamps	4 x 400 watts
Lamps type	LED
Light capacity	4 x 60,000 lumen
Design lifetime	50000 hours
Working temperature	-40°C ~ 50°C
Max. Light coverage	5000m² (Horizontal Angle)
Protection grade	IP65

■ Chassis Specification

Tow Hitch type	“O” ring or Ball tow hitch
Brake type	Mechanical hand brake
Trailer structure	Single axle
Tire size	14 inches
Leveling jack type	5 x Manual

■ Controller Panel Specification


Control module	SMARTGEN HGM1790N
Main & Lamps Breaker	DELIXI
Emergency stop	Equipped
Starting method	Electric (Key start/Button))
Output Socket	2 x Single phase

LED Lights Detailed Technical Data

Image




Dimension



Description	LED Floodlights
Model number	JR328-400W
Light power	400W LED
Installation method	“U” type holder
Working temperature	-40℃ ~ 50℃
Rated voltage	AC 100-277V
Rated frequency	50/60Hz
Power factor	≥0.95
Design lifetime	50000 hours
Protection grade	IP65
Certificates	3C, UL, CE
Light cover material	Aluminum
Radiate unit	Aluminum radiator
Lighting angle	25° , 40° , 60° , 90° , 110°
Luminous efficacy	150Lm/W
Luminous flux	60000Lm@5000K
Color temperature	5700±300K
Color rendering index	RA≥70@5000K

Lighting Performance



Standard Supply Scope

- Industrial exhaust silencer
 - Maintenance free battery
 - Water cooling radiator
 - A.V.R
 - Weatherproof canopy
- Flexible pipes
 - Battery wires
 - Wiring diagram
 - Build-in based fuel tank
 - Top caution light
- Float Battery charger
 - Manual books
 - Ball/Ring hitch with safe chain
 - Emergency stop button
- Base frame
 - Digital control panel
 - Main circuit breaker
 - Power output socket x 2

Optional Supply Scope

Engine	AC Alternator	Control Panel	Lamps	Others
○ Kubota D1105-E2BG ○ Yanmar 3TNV76 ○ Yanmar 3TNV88 ○ Quanchai QC380D	○ Stamford ○ Mecc Alte	○ Smartgen ALC404 ○ Smartgen ALC704 ○ Smartgen ALC708 ○ ComAp LTC 80 ○ Wi-Fi router (4G SIM) ○ Remote control & monitoring system	○ 4x1000W MH lamps ○ 4x350W LED ○ 4x480W LED	○ Security camera ○ Grounding rod ○ Water-jacket heater ○ Battery isolator ○ Fire Extinguisher ○ Wheel chocks ○ Reflector set ○ Trailer VIN number ○ Spark arrestor muffler

GLT1600L-8HP

Powered by  Perkins

Control Panel

Configuration
● Emergency stop button
● Protection MCB + Lamps & Socket circuit breaker
● Digital control module
● Power output socket x 2 (Single Phase)
● Controller box
● Alarm buzzer



Key Features
● Large back-lit icon LCD display
● Single / Three phase generator monitoring
● AC phase voltage display
● Generator frequency display
● Engine speed RPM display
● Battery voltage Vdc display
● Generator running hours display
● Engine coolant temperature display
● Engine oil pressure display
● Pre-alarm & shutdown alarm function
● Low oil pressure shutdown alarm
● Engine high temperature shutdown alarm
● Engine over speed shutdown alarm
● Generator over/under voltage shutdown alarm
● Generator overload shutdown alarm
● Start/Stop failure shutdown alarm
● IP65 rating offers increased resistance to water ingress

Control Module: SMARTGEN HGM1790N	
Digital input	5
Relay output	5
Communication interface	PC
AMF	N/A
AC System	1P2W / 2P3W / 3P3W / 3P4W
Phase voltage input	0-300Vac
Frequency range	3Hz ~ 70Hz
Standby current	TBA
Accuray	1%
Control relay outputs	3A/30Vdc
DC supply	DC 8-35V
Operating temp.	-20 ~ +70℃

Controller Module Options

Smartgen	Smartgen	ComAp
ALC404	ALC704/708	IntelLite LTC 80
		

Local Distributor / Partner

